

## Wälzlagerfett KP2K-30 Roller Bearing Grease KP2K-30

### DESCRIPTION

Liqui Moly Roller Bearing Grease KP2K-30 is a high-quality, lithium-calcium soap grease for lubricating roller and plain bearings at increased temperatures and under extreme loads. As well as anti-corrosion and anti-oxidant additives, this grease also contains EP additives which give it optimum lubrication properties. The product is still fully effective in the presence of up to 20 % water.

Corresponds to and fulfills the following classifications and specifications:

Labeling according to	DIN 51502:	KP2K-30
-----------------------	------------	---------

### TECHNICAL DATA

Appearance and consistency	: Natural color, soft and pliable	
Saponification type	: Li-Ca	
Temperature range	: -30 – 130 °C	
NLGI	: 2	DIN 51 818
Worked penetration	: 275 – 295 1/10 mm	DIN ISO 2137
Flow pressure -30 °C	: <1400 hPa	DIN 51 508
Oil separation		
After 18h at 40 °C	: 1,8 %	DIN 51 817
After 7 days at 40 °C	: 5,9 %	
Corrosion protection properties		
EMCOR method	: Corr. char. 0	DIN 51 802
Copper corrosion 24h 100 °C	: 1-b	DIN 51 811
Behavior in the presence of water	: 1-90	DIN 51 507 T1
Base oil viscosity 40 °C	: 200 mm <sup>2</sup> /s	DIN 51 562
Base oil viscosity 100 °C	: 16,0 mm <sup>2</sup> /s	

### ART OF USE


For the assembly, maintenance and repair of motor vehicles, machine tools, construction machinery and presses. For High load bearings and joints, splined shafts, threads and guides.

### AVAILABLE PACK SIZE


Roller Bearing Grease KP2K-30	15 kg	Part no. 4192
	25 kg	Part no. 4193
	50 kg	Part no. 4194
	180 kg	Part no. 4195

PI 02/05/10

**Our information is based on thorough research and may be considered reliable, although not legally binding.**



# PRODUKTTINFORMATION



LIQUI MOLY GMBH  
Jerg-Wieland-Str. 4  
D-89081 Ulm-Lehr

Postfach 28 29  
D-89018 Ulm  
[www.liqui-moly.de](http://www.liqui-moly.de)

Phone: +49-(0)731/1420-13  
Fax: +49-(0)731/1420-82  
e-mail: [info@liqui-moly.de](mailto:info@liqui-moly.de)

Service Hotline: 0800/8323230  
Technische Hotline: +49-(0)731/1420-13